

Specifications

Model / MFs4		
Type		Four Stroke
Maximum output	HP (kw)	4 (2.9)
Maximum operating range	rpm	4500-5500
Fuel consumption at W.O.T	L/Hr (Gal/Hr)	1.5 (0.4)
Number of cylinder		1
Bore x Stroke	mm (in)	59 x 45 (2.32 x 1.77)
Displacement	cc (Cu in)	123 (7.5)
Compression (Without De-comp.)	kpa (kg/m ²)	290 (3.0) (780 (8.0))
Engine lubrication system		Trochoid pump
Starting system		Manual
Spark plug		NGK DCPR6E
Ignition timing	degree	BTDC0° - BTDC25°
Alternator output		(Option 12V 60W 5A)
Engine oil		NMMA Certified FC-W® 4-Stroke Oil
Engine oil capacity	L (Gal)	0.45 (0.12)
Fuel tank capacity	L (Gal)	1.15 (0.3)
Speed control		Twist grip type
Gear reduction ratio		2.15 (13:28)
Emission Compliance		EPA & CARB 3-Star

Specifications and descriptions are subject to change without notice.

Standard & Optional Equipments

Type	DS / DL
Electric Starter	-
Manual Recoil Starter	●
Decompression Release	●
Engine Stop Switch Lanyard	●
Alternator	○
Rectifier	○
Dual Tank Connector	●
Transom	15 / 20
Propeller	●
Analog Tachometer	-
Analog Trim Meter	-
Remote Control Box	-
12L Plastic Fuel Tank	○
1.15L In-Tank	●
Tool Kit	●
Emergency Starter Rope	●
Spare Spark Plugs	●
Owners Manual	●

Specifications

Model / MFs5		
Type		Four Stroke
Maximum output	HP (kw)	5 (3.7)
Maximum operating range	rpm	4500-5500
Fuel consumption at W.O.T	L/Hr (Gal/Hr)	1.7 (0.45)
Number of cylinder		1
Bore x Stroke	mm (in)	59 x 45 (2.32 x 1.77)
Displacement	cc (Cu in)	123 (7.5)
Engine lubrication system		Trochoid pump
Starting system		Manual
Spark plug		NGK DCPR6E
Ignition timing	degree	BTDC0° - BTDC25°
Alternator output		(Option 12V 60W 5A)
Engine oil		NMMA Certified FC-W® 4-Stroke Oil
Engine oil capacity	L (Gal)	0.45 (0.12)
Fuel tank capacity	L (Gal)	12 (3.17)
Speed control		Twist grip type
Gear reduction ratio		2.15 (13:28)
Emission Compliance		EPA & CARB 3-Star

Specifications and descriptions are subject to change without notice.

Standard & Optional Equipments

Type	DS / DL	SS / SL
Electric Starter	-	-
Manual Recoil Starter	●	●
Decompression Release	●	●
Engine Stop Switch Lanyard	●	●
Alternator	○	○
Rectifier	○	○
Dual Tank Connector	●	-
Transom	15 / 20	15 / 20
Propeller	●	●
Analog Tachometer	-	-
Analog Trim Meter	-	-
Remote Control Box	-	-
12L Plastic Fuel Tank	○	●
1.3L In-Tank	●	-
Tool Kit	●	●
Emergency Starter Rope	●	●
Spare Spark Plugs	●	●
Owners Manual	●	●

● Standard ○ Optional

Specifications

Model / MF36		
Type		Four Stroke
Maximum output	HP (kw)	6 (4.4)
Maximum operating range	rpm	5000-6000
Fuel consumption at W.O.T	L/Hr (Gal/Hr)	2.0 (0.53)
Number of cylinder		1
Bore x Stroke	mm (in)	69 x 45 (2.32 x 1.77)
Displacement	cc (Cu in)	123 (7.5)
Engine lubrication system		Trochoid pump
Starting system		Manual
Spark plug		NGK DCPR6E
Ignition timing	degree	BTDC0° - BTDC25°
Alternator output		(Option 12V 60W 5A)
Engine oil		NMMA Certified FC-W® 4-Stroke Oil
Engine oil capacity	L (Gal)	0.45 (0.12)
Fuel tank capacity	L (Gal)	12 (3.17)
Speed control		Twist grip type
Gear reduction ratio		2.15 (13:28)
Emission Compliance		EPA & CARB 3-Star

Specifications and descriptions are subject to change without notice.

Standard & Optional Equipments		
Type	DS / DL	SS / SL
Electric Starter	-	-
Manual Recoil Starter	●	●
Decompression Release	●	●
Engine Stop Switch Lanyard	●	●
Alternator	○	○
Rectifier	○	○
Dual Tank Connector	●	-
Transom	15 / 20	15 / 20
Propeller	●	●
Analog Tachometer	-	-
Analog Trim Meter	-	-
Remote Control Box	-	-
12L Plastic Fuel Tank	○	●
1.15L In-Tank	●	-
Tool Kit	●	●
Emergency Starter Rope	●	●
Spare Spark Plugs	●	●
Owners Manual	●	●

● Standard ○ Optional